

USER MANUAL

Exclusive 3 channels camera



Please download WIFI products (No download required for non WIFI) the hot spot of the machine

- Product Specification

DDR	Built-in 64M
FLASH	8M SPI norflash
Display Screen	2.0 inch IPS HD screen
LCD resolution	800X480 pixels
	MINI USB 5V/2A power adapter port
External port	Max support 32G Class10 TF card
	2.5mm digital 720P rear view lens port
Speaker	Monophonic 15*10mm speaker
MIC	4015 Standard Omnidirectional Microphone
Features:	
Front camera	6-glass/F2.0aperture/170°wide angle
Inside camera (optional)	VGA 120°
GPS tracker	NO
AV OUT	NO
Rear camera	6M cable/2.5mm port
Photo	Support
Lens rotates	Adjust manually
WDR	Support
HDR	Support
Reversing visual	Support
Video format	AVI
Image format	JPG
Compression format	H.264
Battery	150 mAh polymer lithium battery
Language	support multi-language
G-sensor	Support

Motion Detection	Support	1) Menu/C
Delay shutdown	Support	3) Down
	Support, Do not leak seconds	5) Up
Loop recording		7) Micropho
Sound record	Support	9) Holder in
Fill light for night vision	Support(Open manually)	11) Power in
Parking monitoring	Support	13) Display
Front camera	Max 1680x960 (30f/s)	15) Turn nig
In-car camera resolution	HD640x480 (25f/s)	(O) Power button on/off the device.
Camera resolution	Max support 3M	[M] Menu/camera
Vorking Envi	ronment	Press [OK] key to [OK] to take pho
Operating temperature	-40°C~70°C	mode, press [Ol
Operating humidity	15-65%RH	recording, short pre video file, and this
Storage temperature	-40°C~70°C	In video mode ,long j



1) Menu / Camera / Playback 2) Power button 3) Down

4) Confirm button

6) Front camera 7) Microphone

8) Reset button

10) Rear camera interface

12) TF Card slot

11) Power interface

13) Display screen 14) Inside camera(optional)

15) Turn night vision on / off [O] Power button, short press to turn on/off screen, long press to switch

[M] Menu / camera / playback button

9) Holder interface

Press [OK] key to stop recording, press [M] to enter photo mode, press [OK] to take photo: In the camera mode, press [M] to enter playback mode, press [OK] key to playback. Lock function: In case of video recording, short press [M] for a key lock function to protect the current video file, and this file will not be covered by the cycle video

		Recorder	Menu
1	Resolution	1080P FHD/720P/VGA	
2	Loop recording	Off/1minutes/2minutes 3minutes	
3	High dynamic range HDR	on/ off	Improved image quality, Better visual effect
4	Exposure compensation	-321.0.1.2.3	
5	Motion detection	on/ off	In standby mode, it will automatically record while a objective moves
6	Sound record	on/ off	Turn on/off sound record
7	Time stamp	on/ off	
8	Car number	on/ off	
9	G-sensor	High/Medium/Low Sensitivity	When car occur collision/accident, it will local current video and can't be covered
10	Parking monitor	on/ off	unattended surveillance
11	Date/time	Adjustment Years months date/hours Minutes seconds	
12	Automatic shut-down	Off/3minutes/5minutes 10 minutes	
13	keypad tone	on/ aff	
14	OSD language	Support multilingual	Choose a language

15	Light source frequency	50HZ/60HZ	Choose the Light source frequency
16	format	Confirm/ cancel	format TF card
17	Screen saver	Off/30seconds/1minute / 2minutes	
18	Default setting	Confirm/ cancel	
19	version	Machine software version number	

In photo mode ,long press [M] to enter photo menu settings as follows:

1	Shooting method	Single shooting/2 seconds timer / 5 seconds timer / 10 seconds timer
2	Resolution	1M/2M/3M
3	Continuous shooting	on/ off
4	Picture quality	High quality/standard/economy
5	Acutance	Strong/standard/soft
6	White balance	Automatic/sunlight/cloudy/tungsten lamp/fluorescent lamp
7	ISO	Automatic/100/200/400
8	Exposure compensation	-3, -2, -1, 0, 1, 2, 3
9	Time stamp	Off/Date

I ➤ IDown key, short press I ➤ I to select function at the Menu interface, short press button to turn on/off sound record at the shooting interface.

[◀] Up key. 1, short press [◀] to select function at the Menu interface: 2. In case of video recording, short press OK button to pause, then short press I ∢ 1 button to switch frontinside view image (require inside view lens); 3. long press [◀] button to switch front-rear view image; 4. In case of front-rear view image, short press OK button to pause, then short press [∢]button to switch front-rear view image (require rear view lens)

LOKI Confirm button short press to confirm in the menu interface, short press to video record on off in the video mode

In case of video recording. 4 pin plug of rear view lens insert AV-in hole of device, there's a rear view image in topright of the screen, that means connected successfully; short press OK button to pause, long press [◀] button to switch front-rear view image, When hang up "R" gear, it will show full image of rear view

Note: This device can only support dual cameras to video record at the same time instead of 3 channels camera, that is front-inside camera or front-rear camera; if installed a rearview

camera and choose front-inside view mode, it will automatically indicate full image of car reversing visual when you hang up 'R' gear, but won't effect front-inside video record, also will automatically switch back front inside view effect cancel 'R' gear.

As for system update to support 3 channels camera to video record at the same time, please prevail in kind and we're sorry for no further notice.

If the recorder crashes and accidental operation is not a normal fault, press 【RESET】 to shutdown the device, then press 【OK】 to reboot the device.

Installation Notes

1. Please test the rear view camera firstly, if it works well then install (package without rear

view lens can be ignored).

2. Turn off the car engine.

3. The TF card insert the recorder slot. [Note] Please use the high-speed TF card (Class10 above), capacity of not less

than 4GB, TF card maximum support 3CBB.

4. The recorder via a bracket fixed to the front windshield of the car.

5. Insert the car charger into the car cigarette lighter.

[Note] When wiring, extend the charging line along the edge of the car door frame.

and carpet under the car laying.

6. Install the rear camera at the rear of the vehicle, and pay attention to the up and down direction. Writing can be burled along the edge of the car roof laying. I Note I There are two ways to install the rear camera:

Adsorbed on the glass above and behind the car, hands-on self-installation

(Reversing visual function can not be achieved, only real-time recording rear video). To find a professional installation staff installed in the license plate above the camera at the same time need to connect the power reversing lights. (Reversing visual function can be achieved)

Adjust the lens position to ensure the best viewing angle.
 Start the engine and check that the machine is operating properly.

Features

1. Use the automatic recording function 1.Use the automatic recording function
Start the care regine, the recorder automatically starts to open the recording function
Close the car engine, The recorder automatically saves the contents of the log and shuts
down. recorded vides segments are stored on the TF card. When the TF card is full, the
recorder will overwrite the oldest recorded image preferentially.

[Note]

in Time segment of record can be set 1/2/3 minutes in the menu .

The video individually saved in the folder named "DCIMA" and "DCIMB" in TF card (package include rear view lens).

3. Use motion detection

3. Ose motion detection in standby mode, enter the menu screen open the motion detection mode. When the lens is sensitive to the peripheral area of a moving object, the state machine into the camera, recording 30 seconds after the system stops recording To exit the motion detection mode, in standby mode to enter the menu screen close motion detection mode.

4. G-sensor The built-in gravity sensor (G-sensor), if serious vehicle collision, the recorder will lock the first 5 seconds and 10 seconds after the image date when the accident occurred while the bottom left of the display screen displays a lock icon; locked images will be saved as a special file, the file

will not be overwritten cycle. (note) Gravity sensor (G-Sensor)sensitivity adjustment support may actually

need to change setting in the setup menu according to their image.

- 5. The device has a key lock feature that will need to retain an image without being locked loop overwritten. In the video mode, short press [M] key logger will then lock the entire video image.
- In shooting mode, Press the [M] key to enter the menu setting, find the date/time menu, short press the [OK] button to confirm and return to the setup menu settings, press the [M] key to exit the menu setting. [note] in order to effectively record the date and time traffic safety accident forensics, before using the menu setting.

In the playback mode, press the {OK} key to play back. To exit playback mode, press MODE button again.

8. Reversing visual function

First , you must connect the dvr with car charger, rear-view camera connect the reversing lights. Insert the car charger, machine will automatically start recording status, screen switch R position in the recording mode automatically switches to the rear-view camera, display reverse image. After reversing visual machine automatically return to video mode.

Reminder: Please test the rearview camera is normal before installation.

9. Parking monitor(To achieve unattended surveillance video)

To achieve this function must be connected to the machine in the case of electricity, in the main menu to open the motion detection and parking monitoring function, in the standby state of the vehicle under vibration or moving objects in front, the recorder according to G-sensor to sense automatically start the machine and automatically locks the video for 30 seconds, and automatically save the video file, the video 30 seconds after 5 seconds without the operation will automatically shut down.

Inote I This function is only used when stopping. Please turn off the motion detection and stop monitoring function during normal driving.

	FAQ
Machine appears "file error" message	Settings menu -> Restore factory settings and format the memory card,the general problem is TF card
The screen appears horizontal stripes interference	Please select the correct power supply frequency 50HZ(PAL)
How to properly turn on the 24-hour parking monitoring function	While in normal driving, please do not open, it is easily lead to automatic shutdown or crash, after parking is required to open, configure the buck line or mobile power please

Night shooting screen is not clear enough	Recorder shooting depends on the outside strong light source (such as streetlights or car light)
The machine always reverts to the default date and time	Shutdown in the first case full of electricity, you can use car charger or mobile power supply to add power
what is the reason for video file leak seconds	(Turn off motion detection/Turn on the loop recording function) With a certain choice of their own genuine card C10 high-speed card
Why during recording, the machine automatically shut down suddenly	Please turn off the parking monitoring function first/Ambient temperature exceeds 70 ℃ will cause automatic shutdown
[Note] Practice proof	Most of the problems sources from the memory card,

The information provided in this manual is for reference only. Please prevail in kind (some special features depend on different models). All rights reserved.